Lab D Cleanroom Detector assembly and characterization

Micro-detector assembly is accomplished using optical *coordinate measuring machines (CMMs)* with magnification of over 1000x in order to achieve micron accuracy during assembly of components. Lab D teams interface with designers, engineers, and physicists from Fermilab and as well as from other laboratories to address the R&D phase, reviewing, modifying (when necessary) and implementing all fixturing for component sub-assemblies to barrel assemblies. Once all R&D procedures are proven and finalized, the teams are responsible for production and final assembly of the detectors.

Lab D has four *probe stations* enabling precision measurements of integrated circuits at the wafer level.


Past and present Fermilab projects include CDF, D0, DES, CMS FPIX & TOB. Projects for other labs include STAR (BNL), Phenix VTX & FVTX (BNL), SVT (JLab)

CORDAX 1808

There are 3 CORDAX 1808 machines in Lab D

- Optical CMM (originally touch probe)
- Manual motion
- Computer readout







OGP (Optical Gaging Products) Video Inspection System

There is one OGP system in Lab D

- Optical CMM (touch probe option)
- Autofocus and motion control
- Computer readout



ZEISS UMM 500

There are 2 Zeiss UMM 500 machines in Lab D


- Optical CMM (touch probe option)
- Computer readout



Cascade Microtech probe station

There is one Cascade Microtech probe station in Lab D


- Automated
- Cooling
- Computer control and readout



Probe stations

There are 3 smaller probe stations

Computer readout



Encapsulation tool, imaging microscopes, vacuum ovens, sonic cleaners

Additional support equipment available in Lab D

- Encapsulation tool
- Programmable vacuum ovens
- Imaging microscopes
- Sonic cleaner





Encapsulation tool

Vacuum oven